



1235 x 200 x 6 mm - 1815 x 200 x 5 mm - 620 x 450 x 6 mm



1. Protezione Hot Coating
Hot Coating protection
2. Stampa digitale
Lightfast digital print
3. Sughero > 600 kg/m³
Cork > 600 kg/m³



Classe di utilizzo / Classification	EN 16511	23/33	23/33
Dimensioni / Dimensions	EN 427 / EN 428	1235 x 200 mm - 620 x 450 mm	1815 x 200 mm
Spessore totale (compreso mat. fonoassorbente) / Thickness	EN 428	6 mm	5 mm
Peso / Weight	EN 430	ca. 3 kg/m ²	
Certificazione acustica / Acoustics Performance	EN ISO 717-2	17 dB	
Stabilità dimensionale / Dimensional Stability	EN 434	< 0,10%	
Impronta residua / Residual Indentation	EN 433	max 0,25 mm	
Resistenza alle rotelle delle sedie da ufficio / Effect of castor chair	EN 425	Tipo W / W type	
Resistenza agli agenti chimici / Resistance to chemicals	EN 423	Molto buona / Very good	
Valore di rigonfiamento del pannello dopo 24 h / Water Resistant test	EN 317	< 0% (waterproof)	
Resistenza termica / Thermal Resistance	EN 12524	0,06 m ² K/W	
Resistenza al peso / Weight Resistance	EN 51130	2.000 / 14 mm	

		PACCO / BOX			PALLET		
		Doghe/planks	Peso/weight	Superficie/surface	Pacchi/packs	Peso/weight	Superficie/surface
PRINTCORK DIGITAL GLUEDOWN WALL	1235 x 200 x 6 mm	11 pz/pcs	8,16 kg	2,72 mq/sqm	52 pz/pcs	424 kg	141,44 mq/sqm
	1815 x 200 x 5 mm	10 pz/pcs	10,16 kg	3,63 mq/sqm	48 pz/pcs	488 kg	174,24 mq/sqm
	620 x 450 x 6 mm	10 pz/pcs	8,37 kg	2,79 mq/sqm	60 pz/pcs	502 kg	167,40 mq/sqm